

BDA Series

• 105°C 2,000Hrs assured.

Solvent-proof

BDS
(MVK)

Long Life

BDA

- Vertical SMD type.
- Long Life.
- For LED MT/TV, Copying Machine.
- RoHS compliant.
- Halogen-free capacitors are also available.

**SPECIFICATIONS**

Item	Characteristics							
Rated Voltage Range	4 ~ 50 V _{DC}							
Operating Temperature Range	-40 ~ +105°C							
Capacitance Tolerance	±20%(M) (at 20°C, 120Hz)							
Leakage Current	I=0.01CV(μA) or 3μA, whichever is greater. Where, I:Max. Leakage current(μA), C:Nominal capacitance(μF), V:Rated voltage(V _{DC}) (at 20°C, 2 minutes)							
Dissipation Factor(Tanδ)	Rated voltage(V _{DC})	4	6.3	10	16	25	35	50
	Tanδ(Max.)	0.37	0.28	0.24	0.20	0.16	0.13	0.12
(at 20°C, 120Hz)								
Temperature Characteristics (Max. Impedance ratio)	Rated voltage(V _{DC})	4	6.3	10	16	25~50		
	Z(-25°C)/Z(20°C)	6	3	3	2	2		
	Z(-40°C)/Z(20°C)	12	8	5	4	3		
(at 120Hz)								
Load Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied for 2,000 hours at 105°C.							
	Rated voltage(V _{DC})	4 ~ 16			25 ~ 50			
	Capacitance change	≤ ±25% of the initial value			≤ ±20% of the initial value			
	Tanδ	≤ 200% of the initial specified value						
	Leakage current	≤ The initial specified value						
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.							
	Rated voltage(V _{DC})	4 ~ 16			25 ~ 50			
	Capacitance change	≤ ±25% of the initial value			≤ ±20% of the initial value			
	Tanδ	≤ 200% of the initial specified value						
	Leakage current	≤ The initial specified value						
Others	Satisfied characteristics KS C IEC 60384-4							

PART NUMBERING SYSTEM

BDA	16	VC	100	M	F60	TP	
							With tape
							Case code
							Capacitance tolerance(±20%)
							Nominal capacitance code (ex. 0.1μF:R1, 1.0μF:1, 4.7μF:4R7, 10μF:10)
							Lead type
							Rated voltage
							Series name

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

Cap.(μF)	Freq.(Hz)			
	120	1K	10K	100K
1	1.00	1.50	1.75	1.80
2.2 ~ 10	1.00	1.30	1.40	1.50
22 ~ 100	1.00	1.05	1.08	1.08

DIMENSIONS OF BDA Series

Unit(mm)

DIMENSIONS

MARKING

Note 1 : 4×5.2(D55), 5×5.2(E55) is excluded symbol mark.
 Note 2 : 6.3WV is marked by 6V.

Case code	Ø D	L	A	B	C	W	P	a	b	c
D55	4	5.2	4.3	4.3	5.1	0.5~0.8	1.0	1.0	2.6	1.6
E55	5	5.2	5.3	5.3	5.9	0.5~0.8	1.4	1.4	3.0	1.6
F55	6.3	5.2	6.6	6.6	7.2	0.5~0.8	1.9	1.9	3.5	1.6
F60	6.3	5.7	6.6	6.6	7.2	0.5~0.8	1.9	1.9	3.5	1.6

Recommended solder land on PC board

: Solder land on PC board

RATINGS OF BDA Series

V _{DC} μF	4		6.3		10		16		25		35		50	
1													D55	5.6
2.2													D55	10
3.3													D55	14
4.7									D55	13	D55	15	E55	19
10							D55	16	E55	25	E55	25	F55	29
22	D55	19	D55	21	E55	30	E55	30	F55	40	F55	40		
33	E55	30	E55	34	E55	34	F55	45	F55	45				
47	E55	34	E55	36	F55	48	F55	48	F60	52				
100	E55	45	F60	56	F60	90	F60	110						

↑
 ↑
 Rated Ripple Current (mA_{rms}/105°C, 120Hz)
 Case code